

FLEXIBELE LED-SIGNALISATIE

30022-011


FLEX LED | GREEN | 10mm x 10mm | 1m | M12

GREEN



M12 Connector

Pin Assignment

			
M 12 male connector			
RGBW	RGB	Mono RED	Mono GREEN
1 = Green	1 = Green	1 = N/C	1 = Green
2 = Blue	2 = Blue	2 = N/C	2 = N/C
3 = 24VDC	3 = 24VDC	3 = 24VDC	3 = 24VDC
4 = Red	4 = Red	4 = Red	4 = N/C
5 = White	5 = N/C	5 = N/C	5 = N/C

Specificaties

Aansluiting	M12 (A-code), 4-pin
Aantal LEDs	120 LEDs/m
Afmetingen	10mm x 10mm
Buigradius	150mm
Certificaten, keurmerken, markeringen	CE, RoHS
Dimbaar	Ja, via PWM
Gebruikstemperatuur	-40°C tot +55°C
IP-aanduiding	IP67, IP69
Kleur	Wit
Kleur LEDs	Groen
Kleurweergave index	>80
Kniplengte	100mm
Lengte	1m
Levensduur LEDs	70 000h @ 25°C

Lichtstroom	550lm/m
Materiaal	Siliconen
Merk	4K
Oriëntatie LEDs	Direct
Oriëntatie lichtvlak	Frontaal
Slagvastheid	IK08
Spanning	24V DC
Stralingshoek	120°
Stroomverbruik	10W/m
Type	LED-flex verlichting
UV-Bestendig	Ja