

D1xB2X15DC024
MB1A1R/C

Xenon baken | ATEX | 15J | 24V DC | wit



Specificaties

Aansluiting	0,5-2,5mm ² (20-14 AWG)
Afmetingen	Ø150mm x 253mm
Bedrijfsspanning	18-30V DC
CE-certificaat	Ja
Certificaten, keurmerken, markeringen	UL, cUL, ULC, IECEx, ATEX, CCCEX, Ex EAC, PESO, CSFM, SIL1 & SIL2
Codering IECEx/ATEX - GAS	II 2G Ex db IIC T5 Gb Ta -55°C to +80°C (T6 +70°C)
Codering IECEx/ATEX - STOF	II 2D Ex tb IIIC T95°C Db Ta -55°C to +80°C
Energie	15J
Gebruikstemperatuur	-55°C tot +80°C
Gewicht	3,2kg
Goed om te weten	Automatische synchronisatie op systemen met meerdere bakens
IP-aanduiding	IP66 & IP67

Ingangsstroom	500 mA @ 24V DC
Kabelingang	2x 3/4"NPT, 2x M20, 1x 3/4"NPT
Kleur behuizing	Rood
Kleur lens	Wit
Lichteffecten	4 flitspatronen
Lichtsterkte	750cd
Materiaal	Behuizing: LM6 marine grade aluminium, Lens: high impact boriumsilicaat glas, Blindstop: messing, Beschermingsrooster: roestvrijstaal A4 316
Merk	E2S
Model	D1x
Relatieve luchtvochtigheid	Gecoate printplaat, tot 99% RH
Type	Xenon baken