
## LED BEACONS

## SF10-M1JN-B

## Multifunction LED beacon, IP23, Ø100mm, 12-24V DC, cable, blue





## Specifications

Patlite	Material
No	Mounting ar
Yes	Operating te
500mm	Operating vo
CE, cULus, EAC, KC	Particularitie
Blue	
Ø100mm x 141mm	Rated currer
4,5G	Rated voltag
IP23 / IP65 with rubber gasket	Relative hum
100 000h	
Rotating, flashing, pulsing,	UL certificate
dimming and omni- or unidirectional	Voltage
400cd	Weight
	No   Yes   500mm   CE, cULus, EAC, KC   Blue   Ø100mm x 141mm   4,5G   IP23 / IP65 with rubber gasket   100 000h   Rotating, flashing, pulsing, dimming and omni- or unidirectional

Material	Polycarbonate
Mounting and connection type	3-screw mounting/cable
Operating temperature	-20°C to +50°C
Operating voltage	10-30V DC
Particularities	Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute
Rated current	12V DC 0,62A / 24V DC 0,32A
Rated voltage	12-24V DC
Relative humidity	Less than 90% (no condensation) at 20°C
UL certificate	Yes
Voltage	12V DC / 24V DC
Weight	400g