


LED BEACONS

SF10-M1JN-Y

Multi-function LED beacon, IP23, Ø100mm 12-24V DC, cable/yellow



Specifications

| | | | |
|---------------------------------------|--|------------------------------|--|
| Brand | Patlite | Material | Polycarbonate |
| Buzzer | No | Mounting and connection type | 3-screw mounting/cable |
| CE certificate | Yes | Operating temperature | -20°C to +50°C |
| Cable length | 500mm | Operating voltage | 10-30V DC |
| Certificates, quality marks, markings | CE, cULus, EAC, KC | Particularities | Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute |
| Colour lens | Yellow | Rated current | 12V DC 0,62A / 24V DC 0,32A |
| Dimensions | Ø100mm x 141mm | Rated voltage | 12-24V DC |
| Impact resistance | 4,5G | Relative humidity | Less than 90% (no condensation) at 20°C |
| Ingress protection | IP23 / IP65 with rubber gasket | UL certificate | Yes |
| LED life | 100 000h | Voltage | 12V DC / 24V DC |
| Light patterns | Rotating, flashing, pulsing, dimming and omni- or unidirectional | Weight | 400g |
| Luminous intensity | 1100cd | | |