

FLEXIBLE LED SIGNALING

30022-010


FLEX LED | RED | 10mm x 10mm | 1m | M12

RED



M12 Connector

Pin Assignment

			
M 12 male connector			
RGBW	RGB	Mono RED	Mono GREEN
1 = Green	1 = Green	1 = N/C	1 = Green
2 = Blue	2 = Blue	2 = N/C	2 = N/C
3 = 24VDC	3 = 24VDC	3 = 24VDC	3 = 24VDC
4 = Red	4 = Red	4 = Red	4 = N/C
5 = White	5 = N/C	5 = N/C	5 = N/C

Specifications

Beam angle	120°	LEDs orientation	Directly
Bending diameter	150mm	Length	1m
Brand	4K	Light surface orientation	Frontal
Certificates, quality marks, markings	CE, RoHS	Luminous flux	200lm/m
Colour	White	Material	Silicone
Colour rendering	>80	Number of LEDs	120 LEDs/m
Connection	M12 (A-code), 4-pin	Operating temperature	-40°C to +55°C
Cutting length	100mm	Power consumption	10W/m
Dimensions	10mm x 10mm	Type	LED flex lights
Dimmable	Yes, via PWM	UV Resistant	Yes
Impact resistance	IK08	Voltage	24V DC
Ingress protection	IP67, IP69		
LED life	70 000h @ 25°C		
LEDs colour	Red		