

FLEXIBLE LED SIGNALING

30022-011


FLEX LED | GREEN | 10mm x 10mm | 1m | M12

GREEN



M12 Connector

Pin Assignment

			
M 12 male connector			
RGBW	RGB	Mono RED	Mono GREEN
1 = Green	1 = Green	1 = N/C	1 = Green
2 = Blue	2 = Blue	2 = N/C	2 = N/C
3 = 24VDC	3 = 24VDC	3 = 24VDC	3 = 24VDC
4 = Red	4 = Red	4 = Red	4 = N/C
5 = White	5 = N/C	5 = N/C	5 = N/C

Specifications

Beam angle	120°
Bending diameter	150mm
Brand	4K
Certificates, quality marks, markings	CE, RoHS
Colour	White
Colour rendering	>80
Connection	M12 (A-code), 4-pin
Cutting length	100mm
Dimensions	10mm x 10mm
Dimmable	Yes, via PWM
Impact resistance	IK08
Ingress protection	IP67, IP69
LED life	70 000h @ 25°C
LEDs colour	Green

LEDs orientation	Directly
Length	1m
Light surface orientation	Frontal
Luminous flux	550lm/m
Material	Silicone
Number of LEDs	120 LEDs/m
Operating temperature	-40°C to +55°C
Power consumption	10W/m
Type	LED flex lights
UV Resistant	Yes
Voltage	24V DC