

# Elamid plug Hightech

## SCHUKO / French/Belgian standard

1519100







### General information

Item number	1519100
Model	Elamid plug Hightech
Colour	black

### Electrical parameters

Amperage	16A
Voltage	250V
Poles	2P + PE

### Standards/Directives

According to	DIN VDE 0620 / NF C61-314 / NBN C61-112
Standard	SCHUKO / French/Belgian standard
Certification marks	   

### Operating conditions


Storage temperature	-40°C to +80°C
Operating temperature	-30°C to +40°C
Relative humidity	5 to 95%, no condensation
Degree of protection	IP44
Resistance	UV-resistant Highly resistant to most oils, greases, solvents and detergents, hydrocarbons and organic and inorganic bases in usual concentrations

### Materials

Contact Carrier	PA
Housing	PA

### Connecting cable

Cross section	3x0,75mm <sup>2</sup> -3x2,5mm <sup>2</sup>
Cable diameter, dimension a	6-12mm
Insulation strip length sheath, dimension b	39-41mm
Trim L/N, dimension c	0mm
Insulation strip length cores, dimension d	8-10mm




### Connection screws

Max. torque for screws L-N/PE	0,4-0,5 Nm
Screw drive L-N/PE	Combined slot/PZ1
Max. torque for screws housing	0,6-0,7 Nm
Screw drive housing	Combined slot/PZ1

### Additional technical information

Cable gland	Wrench size SW 24 Max. torque: 2,5-3,75 Nm
-------------	---

Subject to modifications



If the application requires extended specifications, we recommend to test the application under real or simulated conditions. Parameters like duration, quantity and temperature will effect the result significantly