


Plug FM45 Cat.5e shielded or unshielded AWG 23 to 26 IP20
568A/B plastic housing R&M



030.5832

DESCRIPTION

- Field terminated RJ45 connector
- Termination of unshielded cable (UTP)
- Termination of shielded cable (STP)
- Approved for solid and stranded wire AWG 23 to AWG 26
- Optional visual colour coding clip
- Plug FM45 Cat.5e
- Plastic housing with nut
- Copper foil
- Installation instructions

TECHNICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
Standard / norm	ISO/IEC 11801 IEC 60603-7-2/3 EN 50173 ANSI/TIA-568.2 PoE (IEEE 802.3af), PoEP (IEEE 802.3at), 4PpoE (IEEE 802.3bt) IEC 60512-00-001/002
Protection class IP	IP 20
Category	Cat. 5e ISO/IEC
Wiring diagram	T568A and T568B
Cable overall diameter	4.5 - 8.0 mm
Number of wires	8
Wire type	Wire or stranded wire
Colour Coding	Yes, optional
Dust Protection	No
Cable Strain Relief	50 N
Re-termination	≥4 according IEC 60352-4 Re-terminations may be performed with wire of either larger or equal size than originally terminated.
Contact Surface	>1.2µm gold over 1.2µm nickel
Contact material	Bronze (CuSn6)
Pollution Degree	2 according to IEC 61010-1
UL Classification	UL94-V0
Wire diameter	Wire: 0.4 - 0.54mm (0.64mm depending on cable construction) Stranded wire: 0.12mm ² - 0.32mm ²

Plug FM45 Cat.5e shielded or unshielded AWG 23 to 26 IP20 568A/B plastic housing R&M

DESCRIPTION	VALUE/VALUE RANGE
-------------	-------------------

Approved wire diameter with insulation 1.6 mm / 0.063 in

Plug type twisted pair RJ45

MECHANICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
-------------	-------------------

Dimensions 59.0 mm x 14.0 mm x 14.6 mm / 2.323 in x 0.551 in x 0.575 in (W x H x D)

Color Plug: transparent
Housing: traffic gray (RAL 7042)

Material Polycarbonate (plug) polyamide (housing)

Mating Cycles > 750

CLIMATIC DATA

DESCRIPTION	VALUE/VALUE RANGE
-------------	-------------------

Operation temperature -20 °C to +70 °C / -4 °F to +158 °F

ELECTRICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
-------------	-------------------

Contact Resistance Wire - IDC < 1mΩ
Stranded wire - IDC < 5mΩ
Signal contact - screen < 20mΩ

Input-Output Resistance 100 mΩ

Insulation Resistance > 1GΩ (100V)

Dielectric Strength Contact - contact > 1000VDC
Shield - contact > 1500VDC, 1min.

Nominal Current 1.55A @20°C

Overvoltage Category I according to IEC 60664-1

Field-terminated RJ45 plug connector, shielded and unshielded, Cat.5e 8-pole, terminated in IDC technology, suitable for solid or stranded wires, 2- to 8-wire conductors of diameter AWG 23 to AWG 26 (AWG 23/7 - 26/7), housing IP20, for cable diameters of 4.5mm to 8.0mm, coding in acc. with TIA 568A/B.

OPTIONAL ACCESSORY

**Plug FM45 Cat.5e shielded or unshielded AWG 23 to 26 IP20
568A/B plastic housing R&M**

FOTO	DESCRIPTION	PU	PRODUCT NO.
	Clip Security Level 1 FM45 Plug IP20 anthracite plastic housing R&M	10 pcs	R311561
	Clip Security Level 1 FM45 Plug IP20 blue plastic housing R&M	10 pcs	R311580
	Clip Security Level 1 FM45 Plug IP20 brown plastic housing R&M	10 pcs	R311569
	Clip Security Level 1 FM45 Plug IP20 yellow plastic housing R&M	10 pcs	R311579
	Clip Security Level 1 FM45 Plug IP20 gray plastic housing R&M	10 pcs	R311570
	Clip Security Level 1 FM45 Plug IP20 green plastic housing R&M	10 pcs	R311577

**Plug FM45 Cat.5e shielded or unshielded AWG 23 to 26 IP20
568A/B plastic housing R&M**

966704005

10 pcs

FOTO	DESCRIPTION	PU	PRODUCT NO.
	Clip Security Level 1 FM45 Plug IP20 red plastic housing R&M	10 pcs	R311571
	Clip Security Level 1 FM45 Plug IP20 violet plastic housing R&M	10 pcs	R311575