



## LED-Maschinenleuchte



|                           |                                            |
|---------------------------|--------------------------------------------|
| <b>Product-Nr.</b>        | 118110-01                                  |
| <b>EAN:</b>               | 4260556622668                              |
| <b>Model:</b>             | TUBELED_40 II Power                        |
| Bestellnummer             | 118110-01                                  |
| Model                     | TUBELED_40 II Power                        |
| Type                      | LED surface-mounted luminaire for machines |
| Illuminant                | SMD LED                                    |
| Power consumption white   | ~12 W                                      |
| Lamp luminous flux white  | 1899 lm                                    |
| Lamp luminous efficiency  | ~155 lm/W                                  |
| Light distribution        | Light Forming Technology                   |
| Light colour              | daylight white (5200 - 5700K)              |
| Connected load            | 24V DC $\pm$ 10%                           |
| Connection (connector)    | M12 A-type encoded                         |
| Degree of protection      | IP67/IP69K                                 |
| Class of protection       | III                                        |
| Glare-free                | diffused safety glass                      |
| Beam angle (optics)       | 100°                                       |
| Operating temperature     | -30... +60 °C (-22... 140 °F)              |
| Farbwiedergabe Ra         | > 85                                       |
| Lamps lifetime            | > 60.000 h (L80/B10)                       |
| Material Gehäuse          | aluminium                                  |
| Cover material            | safety glass, 4 mm (0,16")                 |
| Höhe B x Breite C         | 29 mm x 40 mm (1,14" x 1,57")              |
| Laenge A                  | 280 mm (11,02")                            |
| Weight (net)              | 360 g (~12 oz)                             |
| Gross weight              | 550 g (~19 oz)                             |
| Risk group (DIN EN 62471) | free group                                 |
| Marking                   | CE, UKCA, ETL Listed (5003526)             |
| Dimmable                  | via optional accessory                     |
| Mounting accessories      | optional                                   |
| Made in                   | Germany                                    |