



LED-Maschinenleuchte



Product-Nr.	118510-01
EAN:	4260556622682
Model:	TUBELED_40 II
Bestellnummer	118510-01
Model	TUBELED_40 II
Type	LED surface-mounted luminaire for machines
Illuminant	SMD LED
Power consumption white	~48 W
Lamp luminous flux white	7593 lm
Lamp luminous efficiency	~155 lm/W
Light distribution	Light Forming Technology
Light colour	daylight white (5200 - 5700K)
Connected load	24V DC $\pm$ 10%
Connection (connector)	M12 A-type encoded
Degree of protection	IP67/IP69K
Class of protection	III
Glare-free	diffused safety glass
Beam angle (optics)	100°
Operating temperature	-30... +60 °C (-22... 140 °F)
Farbwiedergabe Ra	> 85
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehäuse	aluminium
Cover material	safety glass, 4 mm (0,16")
Höhe B x Breite C	29 mm x 40 mm (1,14" x 1,57")
Laenge A	1040 mm (40,94")
Weight (net)	1300 g (~46 oz)
Gross weight	1650 g (~58 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003526)
Dimmable	via optional accessory
Mounting accessories	optional
Made in	Germany