



LED-Systemleuchte



Product-Nr.	110914-21
EAN:	4260556623382
Model:	UNILED SL DC
Bestellnummer	110914-21
Model	UNILED SL DC
Type	LED system light and workplace lighting
Illuminant	SMD LED
Power consumption white	~12 W
Lamp luminous flux white	1899 lm
Lamp luminous efficiency	~155 lm/W
Light distribution	direct
Light colour	daylight white (5200 - 5700K)
Connected load	24V DC $\pm$ 10%
Connection (connector)	M12 A-type encoded
Degree of protection	IP50
Class of protection	III
Glare-free	micro prisms
Beam angle (optics)	100°
Operating temperature	-10... +60 °C (14... 140 °F)
Farbwiedergabe Ra	>85
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehaeuse	aluminium
Cover material	micro prisms cover
Hoehe B x Breite C	35 mm x 85 mm (1,38" x 3,35")
Laenge A	295 mm / 325 mm (11,61" / 12,80")
Weight (net)	500 g (~18 oz)
Gross weight	850 g (~30 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003529)
Dimmable	via optional accessory
Mounting accessories	optional
Made in	Germany
Feature	high light diffusion