



LED-Signalleuchte

Product-Nr.	111090-16
EAN:	4260556624525
Model:	SIGNALLED II RGB
Bestellnummer	111090-16
Model	SIGNALLED II RGB
Type	LED surface-mounted light
Illuminant	RGB LED
Power consumption RED	~10,6 W
Lamp luminous flux RED	236 lm
Lampenleistung Gruen	~10,6 W
Lampenlichtstrom Gruen	108 lm
Power consumption BLUE	~10,6 W
Lamp luminous flux BLUE	372 lm
Light distribution	direct
Light colour	RGB colour space (at least 2563 colours)
Connected load	24V DC - 10% +7% (RGB)
Connection (connector)	M12 A-type encoded
Degree of protection	IP54
Class of protection	III
Glare-free	opal white
Beam angle (optics)	120°
Operating temperature	-10... +50 °C (14... 122 °F)
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehaeuse	aluminium
Cover material	polycarbonate, soft
Hoehe B x Breite C	25 mm x 30 mm (0,98" x 1,18")
Laenge A	1020 mm (40,16")
Weight (net)	650 g (~23 oz)
Gross weight	1000 g (~35 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003529)
Dimmable	no
Mounting accessories	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in	Germany
Feature	Signalling via flashing and/or coloured light