





LED Maschinenleuchte



Product-Nr.	154390-01
EAN:	4260556626154
Model:	TUBELED_25 RGB-W
Bestellnummer	154390-01
Model	TUBELED_25 RGB-W
Type	LED surface-mounted light
Illuminant	SMD RGB-W Cluster LED
Lampenleistung Weiss	~14,4 W
Lampenlichtstrom Weiss	~14,4 W
Lampenlichtausbeute Weiss glob	~159 lm/W
Lichtfarbe Weiss	daylight white (5200 - 5700K)
Power consumption RED	~4,3 W
Lamp luminous flux RED	276 lm
Lampenleistung Gruen	~2,9 W
Lampenlichtstrom Gruen	504 lm
Power consumption BLUE	~4,3 W
Lamp luminous flux BLUE	168 lm
Light distribution	direct
Connected load	24 V DC -10 % +7 % (RGB) – 24 V DC ± 10 % (W)
Connection (connector)	M8 B-kodiert
Degree of protection	IP67
Class of protection	III
Glare-free	diffused safety glass
Beam angle (optics)	100°
Operating temperature	-30... +55 °C (-22... 131 °F)
Farbwiedergabe Weiss	>85
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehaeuse	aluminium
Cover material	safety glass, shatterproof
Hoehe B x Breite C	~28 mm x ~23 mm (~1,10" x ~0,91")
Laenge A	540 mm (21,26")
Weight (net)	450 g (~16 oz)
Gross weight	600 g (~21 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003529)
Dimmable	option external, PWM
Mounting accessories	option
Made in	Germany
Feature	RGB-W: Illumination and beacon in one light; connection