



 Darstellbares Farbspektrum /
 Displayable colour spectrum

 Mischfarben werden mit der
 Ansteuerung mehrerer Eingänge
 gleichzeitig erreicht. /
 Mixed colours will be achieved
 with the control of multiple
 inputs simultaneously.


LED-Signalleuchte

Product-Nr.	118190-02
EAN:	4260556623115
Model:	TUBELED_40 II RGB-W ECO
Bestellnummer	118190-02
Model	TUBELED_40 II RGB-W ECO
Type	LED surface-mounted light
Illuminant	SMD RGB-W Cluster LED
Lampenleistung Weiss	~7 W
Lampenlichtstrom Weiss	~7 W
Lampenlichtausbeute Weiss glob	~165 lm/W
Lichtfarbe Weiss	daylight white (5200 - 5700K)
Power consumption RED	~2,2 W
Lamp luminous flux RED	138 lm
Lampenleistung Gruen	~1,4 W
Lampenlichtstrom Gruen	252 lm
Power consumption BLUE	~2,2 W
Lamp luminous flux BLUE	84 lm
Light distribution	light forming technology
Connected load	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector)	M12 A-type encoded
Degree of protection	IP67/IP69K
Class of protection	III
Glare-free	diffused safety glass
Beam angle (optics)	100°
Operating temperature	-30... +70 °C (-22... 158 °F)
Farbwiedergabe Weiss	>85
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehaeuse	aluminium
Cover material	safety glass, shatterproof
Hoehe B x Breite C	29 mm x 40 mm (1,14" x 1,57")
Laenge A	280 mm (11,02")
Weight (net)	350 g (~12 oz)
Gross weight	550 g (~19 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003529)
Mounting accessories	optional
Made in	Germany
Feature	RGB-W: Illumination and beacon in one light