



LED-Industrieleuchte mit Signalfunktion



Product-Nr.	110190-01
EAN:	4260556624600
Model:	INROLED_50 Ecolab RGB-W
Bestellnummer	110190-01
Model	INROLED_50 Ecolab RGB-W
Type	LED tube light
Illuminant	SMD RGB-W Cluster LED
Lampenleistung Weiss	~19 W
Lampenlichtstrom Weiss	~19 W
Lampenlichtausbeute Weiss glob	126 lm/W
Lichtfarbe Weiss	daylight white (5200 - 5700K)
Power consumption RED	~18 W
Lamp luminous flux RED	480 lm
Lampenleistung Gruen	~5 W
Lampenlichtstrom Gruen	710 lm
Power consumption BLUE	~18 W
Lamp luminous flux BLUE	300 lm
Light distribution	direct
Connected load	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector)	M12 A-type encoded
Degree of protection	IP67/IP69K
Class of protection	III
Glare-free	opal white
Beam angle (optics)	100°
Operating temperature	-30... +55 °C (several colours +35 °C) (-22... 131 °F; 95 °F)
Farbwiedergabe Weiss	>85
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehaeuse	polycarbonate, soft, shatterproof with Ecolab coating
Impact-resistant	IK09
Hoehe B x Breite C	Ø50 mm (Ø 1,97")
Laenge A	565 mm (22,24")
Weight (net)	950 g (~34 oz)
Gross weight	1150 g (~37 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003529), Ecolab, HACCP
Mounting accessories	included light holder made of metal-detectable PP
Made in	Germany
Feature	RGB-W: Illumination and beacon in one light