


LED-Signalleuchte



Product-Nr.	110994-13
EAN:	4260556623467
Model:	UNILED SL RGB-W
Bestellnummer	110994-13
Model	UNILED SL RGB-W
Type	LED system and workplace light
Illuminant	RGB SMD + SMD LED
Lampenleistung Weiss	~38 W
Lampenlichtstrom Weiss	~38 W
Lampenlichtausbeute Weiss glob	126 lm/W
Lichtfarbe Weiss	daylight white (5200 - 5700K)
Power consumption RED	~36 W
Lamp luminous flux RED	960 lm
Lampenleistung Gruen	~10 W
Lampenlichtstrom Gruen	1420 lm
Power consumption BLUE	~36 W
Lamp luminous flux BLUE	600 lm
Light distribution	direct
Connected load	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector)	M12 A-type encoded
Degree of protection	IP50
Class of protection	III
Glare-free	opal white
Beam angle (optics)	100°
Operating temperature	-10... +50 °C (14... 122 °F)
Farbwiedergabe Weiss	> 80
Lamps lifetime	> 60.000 h (L80/B10)
Material Gehaeuse	aluminium
Cover material	plastics, soft
Hoehe B x Breite C	35 mm x 85 mm (1,38 x 3,35")
Laenge A	1045 mm (41,14")
Weight (net)	1600 g (~56 oz)
Gross weight	2450 g (~86 oz)
Risk group (DIN EN 62471)	free group
Marking	CE, UKCA, ETL Listed (5003529)
Mounting accessories	optional
Made in	Germany
Feature	RGB-W: Illumination and beacon in one light