

LED Zubehör


LED accessories



F+B Sensor Kabel, 5 m, offene Enden/M12 Buchse, A-kodiert, für 24V

Artikel-Nr.:	201100-04
EAN:	4260556622583

Bestell-Nr.:	201100-04
Modell:	LED2WORK Sensor Kabel, TPE grau, für 24V DC
Bauform:	Sensor Kabel, TPE, grau
Kodierung:	A-kodiert
Geeignet für:	LED2WORK Leuchten 24V DC, außer RGB und RGB-W Leuchten
Anzahl:	1
Länge Kabel:	5 m
Kabelenden:	offene Enden / M12 Buchse, gerade
Polzahl:	4
Bemessungsspannung:	250V
Strombelastung pro PIN:	4000 mA
Umgebungstemperatur:	-40...+105°C
Durchgangswiderstand:	< 0,005 Ω
Isolationswiderstand:	≥10 ⁸ Ω
Material Kabel:	TPE
Material Griffkörper:	Kunststoff, PP, GY
Material Kontaktträger:	Kunststoff, PP, GY
Material Überwurf:	Edelstahl, V4A
Material Dichtung:	EPDM
Material Kontakte:	Metall, CuSn, vergoldet
Normen:	IEC 61076-2-101
Befestigung an Leuchte:	Steckverbinder M12 Buchse, gerade, Dichtung EPDM, Überwurf V4A
RoHS:	1
UL:	1
Schutzart (montiert):	IP65, IP67, IP68
Gewicht:	200 g
Bruttogewicht:	250 g
Besonderheit:	Food+Beverage geeignet, FDA zugelassen




Litzenfarben auf dem Bild können zum aktuellen Originalprodukt abweichen.



Sensor cable for F+B, 5 m (16,4 ft), open/M12 socket, A-type encoded

Item number:	201100-04
EAN:	4260556622583

Order number:	201100-04
Model:	LED2WORK sensor cable, TPE gray, for 24V DC
Type:	sensor cable, TPE, gray
Encoding:	A-type encoded
Suitable for:	LED2WORK 24V DC luminaires, except RGB and RGB-W luminaires
Quantity:	1
Length of cable:	5 m (16,4 ft)
Cable ends:	open ends / M12 socket, straight
Number of contacts:	4
Rated voltage:	250V
Current load per PIN:	4000 mA
Operating temperature:	-40...+105°C (-40... 221 °F)
Resistance:	< 0,005 Ω
Insulation resistance:	≥10 ⁸ Ω
Material cable:	TPE
Materials grip body:	plastics, PP, GY
Material contact carrier:	plastics, PP, GY
Material cap:	stainless steel V4A
Material seals:	EPDM
Materials contacts:	metal, CuSn, gold-plated
Standards:	IEC 61076-2-101
Connection:	connector M12 socket, straight, seal EPDM, cap stainless steel
RoHS:	1
UL:	1
Degree of protection (fitted):	IP65, IP67, IP68
Weight (net):	200 g (~7 oz)
Gross weight:	250 g (~9 oz)
Feature:	especially suitable for Food+Beverage, FDA approved



The wire colours in the illustration may differ from the current original product.